NEW
Side door with thermal break

DURATEC®
MAXIMUM SCRATCH RESISTANCE

Industrial Sectional Doors

With the innovative wicket door with trip-free threshold

4Ddoors
Just Got European

HÖRMANN

Hörmann brand quality	4
Sustainable production	6
Good reasons to try Hörmann	8
Door fixtures and fittings	10
Application areas	12
SPU F42 SPU 67 Thermo	16
APU F42 APU F42 Thermo APU 67 Thermo	20
ALR F42 ALR F42 Thermo ALR 67 Thermo	24
ALR F42 Glazing ALR 67 Thermo Glazing	28
ALR F42 Vitraplan	32
ALR F42 for on-site facade design	36
Wicket doors	40
Side doors	44
Colours	46
DURATEC glazing with scratch resistance	48
Glazing types	50
Thermal insulation	52
Track versions	54
Advanced technology in every detail	56
Safety features	57
Manually operated doors	58
Handles	59
Compatible system solutions Leading photocell, light grille Operators, controls Operator accessories	60 62 66 74
Performance characteristics Construction and quality features	82 84
Hörmann product range	86

Copyright: No part or excerpt may be reproduced without our prior permission.
Subject to changes. The doors shown are example applications – no guarantee.

Image on left: Strassenmeisterei (road maintenance authority) Sion, Switzerland

Hörmann brand quality

Reliable and oriented towards the future

VW original parts logistics, Ludwigsfelde (near Berlin)

In-house product development

At Hörmann, innovation is produced in-house – highly qualified employees of the development departments are in charge of product optimisation and new developments. This results in market-ready, high-quality products that are very popular around the globe.

Modern manufacturing

All of the essential door and operator components, such as sections, frames, fittings, operators and controls are developed and manufactured by Hörmann. This guarantees a high degree of compatibility between the door, operator and controls. Our certified quality management system ensures the highest quality, from development through to production and delivery.

This is Hörmann quality – Made in Germany.

Made in Germany

As Europe's leading manufacturer of doors, hinged doors, frames and operators, we are committed to high product and service quality. This is how we set standards on an international scale.

Highly-specialised factories develop and manufacture construction components that are characterised by excellent quality, functional safety and a long service life.

Our presence in the global economy's key regions makes us a strong, future-oriented partner for industrial and public construction projects.

Energy savings compass
You can find the interactive planning aid on the Internet at www.hormann.co.uk/energysavingscompass

10 YEAR GUARANTEED AVAILABILITY

It goes without saying that spare parts for doors, operators and controls are original Hörmann parts that come with a guaranteed availability of 10 years.

Competent advice

Experienced specialists within our customer-oriented sales organisation support you from the planning stage, through technical clarification up to the final building inspection. Complete working documentation, such as technical manuals, is not only available in printed form, but is also always accessible and up-to-date at www.hoermann.com.

Fast service

Our extensive service network means that we are always nearby and at your service. This is a great advantage for testing, maintenance and repairs.

Sustainable production

For future-oriented construction



EPD industrial sectional doors with PU-foamed steel sections

EPD aluminium industrial sectional doors



Find out more about Hörmann's environmental activities in the "We think green" brochure.

Sustainable production: Industrial sectional doors from Hörmann

Ecological quality
A comprehensive energy management system ensures environmentally friendly production, e.g. by using the heat from the production systems to warm the building.

Economical quality
A long service life and low maintenance costs thanks to the use of high-quality materials, such as DURATEC glazing.

Functional quality
Large, energy-saving glazing, as well as door constructions with thermal breaks, enable optimum energy efficiency in the building.

Process quality
By further processing mono-material plastic waste from the production process, material resources are saved.

Sustainability verified and documented by the IFT in Rosenheim

Hörmann received confirmation of the sustainability of all its industrial sectional doors through an environmental product declaration (EPD) in accordance with DIN ISO 14025 and EN 15804 from the Institut für Fenstertechnik (ift – Institute of window technology) in Rosenheim. The inspection was based on the Product Category Rules (PCR) “Doors and Gates”. Environmentally-friendly production was confirmed by a life-cycle analysis in accordance with DIN EN ISO 14040 / 14044 for all industrial sectional doors.

Sustainable construction with Hörmann competence

Hörmann has already been able to gain great expertise in sustainable construction through various projects. We also apply this know-how to support your projects.

References for sustainable construction with Hörmann

ThyssenKrupp, Essen

dm logistics centre, Weilerswist

Immogate logistics centre, Munich

Nordex-Forum, Hamburg

Unilever Hafen-City, Hamburg

Deutsche Börse, Eschborn

Opernturm, Frankfurt

Skyline-Tower, Munich

Prologis Pineham Sites, Sainsbury

DGNB
Deutsche Gesellschaft für Nachhaltiges Bauen e.V.
German Sustainable Building Council

© ift Rosenheim

Institut Bauen und Umwelt e.V.

U.S. GREEN BUILDING COUNCIL LEED CERTIFIED USGBC

breeam

Good reasons to try Hörmann

The market leader has the innovations

Only from Hörmann



1 A permanently clear view

Maximum scratch resistance
Doors with DURATEC synthetic glazing stand up to tough demands in rough industrial environments, while maintaining their transparency. A special surface coating, similar to that used on car headlights, protects the pane from scratches and damage caused by cleaning over the long-term.

The DURATEC glazing is available as standard and at no extra charge in all sectional doors with synthetic glazing – only from Hörmann.

For further information, see pages 48 – 51.

Take a look at the video at:
www.hoermann.com

Only from Hörmann

2 Efficient thermal insulation

ThermoFrame
Well-insulated industrial sectional doors are essential in heated buildings. Hörmann industrial sectional doors are optionally available with the ThermoFrame frame connection for a thermal break between frame and brickwork. Additionally, lip seals on both sides of the door and a double seal in the lintel area protect from heat or cold loss, increasing the thermal value by up to 21 %.

For further information, see pages 52 – 53.

World's first
Wicket door construction with thermal break, depth 67 mm

EUROPEAN PATENT

Only from Hörmann

3 Practical solutions

Wicket doors with trip-free threshold
The wicket door with extra-flat stainless steel threshold ensures easier passage of pedestrians. For doors with a width up to 5500 mm, the threshold rail is only 10 mm high in the middle and 5 mm high at the edges, reducing the risk of tripping considerably and making it easier to wheel things through. Under certain circumstances, Hörmann wicket doors with trip-free threshold can even be used as escape doors and for barrier-free construction.

For further information, see pages 40 – 43.

Take a look at the video at:
www.hoermann.com

Only from Hörmann

4 Non-contact door monitoring

Leading photocell without surcharge
Power-driven Hörmann industrial sectional doors with WA 400 and ITO 400 operators are equipped with a self-monitoring closing edge safety device with optosensors as standard. You can also select the leading photocell VL 1 for non-contact monitoring of the closing edge without a surcharge. The light grille HLG can also be optionally integrated into the frame.
These solutions offer you increased safety, faster door action and lower inspection and maintenance costs.

For further information, see pages 62 – 63.

Door fixtures and fittings

Section thicknesses, surface finishes and profile types



42 mm, Stucco-textured | 67 mm, Stucco-textured | 42 mm Micrograin | 67 mm Micrograin

PU-foamed sectional doors in 2 surfaces and 2 depths

PU-foamed sectional doors are available either with 42 mm depth or with sections with thermal break and 67 mm depth. For both versions, the door appearance is 100 % matching.

Depth 42 mm
Hörmann sectional doors with 42-mm-thick PU-foamed sections are especially robust, offering good thermal insulation.

Depth 67 mm
with the best thermal insulation
With the SPU 67 Thermo's 67 mm sections with thermal break, you benefit from an excellent thermal value of up to 0.51 W/(m²·K)*. The thermal break between the exterior and interior of the steel sections also reduces the formation of condensation water on the inside of the door.

The surface finish of the sections of steel doors or doors with bottom sections is based on hot-galvanized sheet steel and a high-adhesion primer-coating (2-component PUR) that protect the door against adverse effects of the weather.

Resistant Stucco surface
Additionally, Stucco texturing gives the door surface a uniform structure on which light scratches or traces of dirt are more difficult to see.

Micrograin surface finishes give an elegant look
Micrograin features a smooth surface and characteristic fine lines. This door surface finish harmonises especially well with modern facades that are characterised by their clear formal structure. The inside of the door is Stucco-textured in Grey white, RAL 9002, as standard.

* For a door size of 5000 × 5000 mm with optional ThermoFrame

For best thermal insulation: 67 mm thermal profiles with thermal break

42 mm standard profile



42 mm Thermo profile



67 mm Thermo profile

Glazed aluminium doors in 2 profile types and depths

Standard profile, depth 42 mm
As standard, the glazing frames are produced using high-quality aluminium extrusion profiles that are designed for robust industrial and commercial day-to-day work. The standard profile without thermal break is ideal for buildings that are barely or not at all heated or cooled.

Thermo profile with thermal break, depths 42 mm and 67 mm
The Thermo profiles with thermal breaks on the interior and exterior are the first choice everywhere where the thermal insulation of the building is important. The 67-mm Thermo profile with 3 chamber system is delivered with triple glazing as standard. The 42 mm profile is offered with double glazing as standard. Other glass variants, e.g. climatic glass or synthetic quadruple pane, can further increase the energy efficiency.

Application areas

A matching door version for every purpose

Save energy thanks to thermal insulation

SPU F42
SPU 67 Thermo

Double-skinned steel sectional doors

Page 14

More light in the building

APU F42
APU F42 Thermo
APU 67 Thermo

Glazed aluminium doors with steel bottom section

Page 20

Fitting in modern architecture

ALR F42
ALR F42 Thermo
ALR 67 Thermo

Glazed aluminium doors

Page 24

Maximum transparency for shop windows

ALR F42 Glazing
ALR 67 Thermo Glazing

Aluminium doors with large glazing

Page 28

Elegant eye-catcher

ALR F42 Vitraplan

Exclusively glazed aluminium doors

Page 32

Door and facade design

Aluminium door ALR F42 for on-site cladding

Page 36

SPU F42

Double-skinned steel sectional doors

Logistics buildings and warehouses
Easy and safe passage of pedestrians thanks to the wicket door with trip-free threshold

Commercial buildings
Bring natural light into the building using optional glazing

Everything from one source:
Industrial doors, dock levellers, dock shelters

Agriculture
Robust thanks to PU-foamed panels

Logistics
Operator WA 300 S4 (see page 66),
the affordable solution for logistics doors

SPU 67 Thermo

Double-skinned steel sectional doors with thermal break

Logistics
Excellent thermal insulation with sections with thermal break, depth 67 mm

Fresh logistics
The SPU 67 Thermo door minimises temperature losses at door openings, making it ideal for use in food and cold logistics.

Excellent thermal insulation with a U-value of up to 0.51 W/(m²·K)

Commercial buildings
Easy and safe passage of pedestrians thanks to a wicket door with thermal break and trip-free threshold

Commercial buildings and warehouses
Bring natural light into the building using optional glazing

Double-skinned steel sectional doors

Matching

SPU F42

1 The 42-mm-thick PU-foamed section with finger trap protection is especially robust and offers a good thermal insulation. The door leaf is available in the Stucco-textured and Micrograin surface variants.

SPU 67 Thermo

2 Optimum thermal insulation is achieved with the SPU 67 Thermo, featuring 67-mm-thick sections with thermal break without finger trap protection*. Both surface variants for the door leaf match the SPU F42.

* In the available size range, these doors comply with the requirements in EN 13241-1

Door type	**SPU F42**		**SPU 67 Thermo**	
	without wicket door	with wicket door	without wicket door	with wicket door
Door size				
Max. width (mm)	8000	7000	10000	7000
Max. height (mm)	7500	7500	7500	7500
Thermal insulation EN 13241-1, Appendix B EN 12428 U-value in W/(m²·K) for a door surface 5000 × 5000 mm				
Closed sectional door	1.0	1.2	0.62	0.82
With ThermoFrame	0.94	1.2	0.51	0.75
Section	0.50	0.50	0.33	0.33

Optimum thermal insulation in 2 section surface finishes

The PU-foamed sections are particularly robust and offer good thermal insulation. Especially with the 67-mm-thick sections you benefit from very high thermal insulation, achieved through the thermal break between the interior and exterior of the steel sections. This also minimises the formation of condensation water on the inside of the door. You can choose between Stucco-textured and Micrograin for the surface finish, both without a surcharge. The Stucco-textured surface features uniform ribbing every 125 mm in the section and in the section transition.

Sections with thermal break in SPU 67 Thermo

Stucco-textured



Micrograin

Colour options page 47
Glazings page 48
Safety features in acc. with EN 13241-1, page 57.
Technical data page 82

Example door versions

Door width up to 4500 mm (example 4500 × 4500 mm)



SPU F42, SPU 67 Thermo
Type A section windows
uniform field division



SPU F42, SPU 67 Thermo
Aluminium glazing frames
uniform field division

Door width up to 5500 mm (example 5500 × 4500 mm)



SPU F42, SPU 67 Thermo
Type D section windows
Wicket door to the left



SPU F42, SPU 67 Thermo
Aluminium glazing frames
Wicket door to the left

Door width over 5500 mm (example 7000 × 4500 mm)



SPU F42
Type E section windows
wicket door in the centre



SPU F42, SPU 67 Thermo
Aluminium glazing frames
wicket door in the centre

Clear passage width (LDB)
SPU F42: 940 mm
SPU 67 Thermo: 905 mm

SPU F42 Plus
In the same appearance as sectional garage doors

On request, the SPU F42 Plus is available in the same door styles and surface finishes as Hörmann sectional garage doors.

For more detailed information, please see the Sectional Garage Door brochure.

APU F42, APU F42 Thermo, APU 67 Thermo

Glazed aluminium doors with steel bottom section

Workshops
Matching glazing division for doors with and without wicket doors

Commercial buildings and warehouses
The PU-foamed bottom section can be replaced easily and inexpensively if damaged, for example, by a vehicle.

Protection bollards protect from damage
When used outside, they avoid expensive collision damage to buildings. When used inside, they protect the door tracks from collision damage.

Especially easy to service and repair thanks to robust bottom sections

Workshops
Easy and safe passage of pedestrians thanks to the wicket door with trip-free threshold



Workshops
Large glazings for light in the workspace

Glazed aluminium doors with steel bottom sections

APU F42

1 Thanks to the combination of robust steel bottom section and large glazings, the door is especially stable and lets a lot of light into the building.

APU F42 Thermo

2 The APU F42 Thermo with glazing beads with thermal break and steel bottom section is recommended for high thermal insulation requirements.

APU 67 Thermo

3 The APU 67 Thermo, depth 67 mm, offers excellent thermal insulation thanks to its glazing beads and steel bottom sections with thermal break.

Door type	APU F42		APU F42 Thermo		APU 67 Thermo	
	without wicket door	with wicket door	without wicket door	with wicket door	without wicket door	with wicket door
Door size						
Max. width (mm)	8000	7000	7000	7000	10000	7000
Max. height (mm)	7500	7500	7500	7500	7500	7500
Thermal insulation EN 13241-1, Appendix B EN 12428 U-value in W/(m²·K) for a door surface 5000 × 5000 mm						
Standard double pane	3.4	3.6	2.9	3.1	–	–
With ThermoFrame	3.3	3.6	2.8	3.1	–	–
Standard triple pane	–	–	–	–	2.1	2.3
With ThermoFrame	–	–	–	–	2.0	2.2
Optional climatic double pane, single-pane safety glass	2.5	–	2.0	–	1.6	–
With ThermoFrame	2.4	–	1.9	–	1.5	–

APU 67 Thermo: Excellent thermal insulation with a U-value of up to 1.5 W/(m²·K) for a door size of 5 × 5 m

Robust bottom section

The 750-mm-high bottom section is optionally available in Stucco or Micrograin surface finish without surcharge. The even PU-foaming of the steel section makes it particularly robust. In case of extensive damage, it can be exchanged easily and inexpensively.

Stucco-textured bottom section

Micrograin bottom section

Colour options page 47
Glazings page 48
Safety features in acc. with EN 13241-1, page 57.
Technical data page 82

Example door versions

Door width up to 4500 mm (example 4500 × 4500 mm)



APU F42, APU F42 Thermo,
APU 67 Thermo
uniform field division



APU F42, APU F42 Thermo,
APU 67 Thermo
wicket door in the centre

Door width up to 5500 mm (example 5500 × 4500 mm)



APU F42, APU F42 Thermo,
APU 67 Thermo
uniform field division



APU F42, APU F42 Thermo,
APU 67 Thermo
wicket door to the left

Door width over 5500 mm (example 7000 × 4500 mm)



APU F42, APU F42 Thermo,
APU 67 Thermo
uniform field division



APU F42, APU F42 Thermo,
APU 67 Thermo
wicket door in the centre

Clear passage width (LDB)
APU F42, APU F42 Thermo: 940 mm
APU 67 Thermo: 905 mm

On request, uniform field division is also possible with wicket door.

The field division of the wicket door arrangement is also available for sectional doors without wicket door.

For modernisation or when the matching appearance of the existing sectional doors must be ensured, the APU F42 / APU F42 Thermo is also available with 91-mm-wide rails.

ALR F42, ALR F42 Thermo, ALR 67 Thermo

Glazed aluminium doors

Commercial buildings
Aluminium profiles with thermal break and optional climatic glazing ensure that insulation is improved by up to 55 %.

Permanent clear view with DURATEC glazing for maximum scratch resistance

Workshops
Permanent clear view thanks to standard DURATEC glazing

Fire station buildings
Large glazings offer more light in the building

Collective garages
Variety of infill options, from expanded mesh to perforated sheet infill for door and wicket door (only ALR F42)

Glazed aluminium doors

ALR F42

1 This door features large glazings and a contemporary appearance with aluminium profiles. The DURATEC glazing provides a permanently clear view.

ALR F42 Thermo

2 Thanks to the glazing profiles with thermal break and DURATEC synthetic glazing, the door offers excellent transparency and good thermal insulation.

ALR 67 Thermo

3 The ALR 67 Thermo, depth 67 mm, with thermal break glazing beads is recommended for highest thermal insulation requirements.

Door type	ALR F42		ALR F42 Thermo		ALR 67 Thermo	
	without wicket door	with wicket door	without wicket door	with wicket door	without wicket door	with wicket door
Door size						
Max. width (mm)	8000	7000	7000	7000	10000	7000
Max. height (mm)	7500	7500	7500	7500	7500	7500
Thermal insulation EN 13241-1, Appendix B EN 12428 U-value in W/(m²·K) for a door surface 5000 × 5000 mm						
Standard double pane	3.6	3.8	3.0	3.2	–	–
With ThermoFrame	3.6	3.8	3.0	3.2	–	–
Standard triple pane	–	–	–	–	2.2	2.4
With ThermoFrame	–	–	–	–	2.1	2.3
Optional climatic double pane, single-pane safety glass	2.7	–	2.1	–	1.7	–
With ThermoFrame	2.6	–	2.0	–	1.6	–

Up to 55 % improved thermal insulation: ALR 67 Thermo with climatic glazing and ThermoFrame

The best thermal insulation

For ALR F42 Thermo and ALR 67 Thermo, the aluminium profiles have a thermal break and offer optimum thermal insulation while letting in the maximum of natural light.
The ALR 67 Thermo with optional climatic glazing and ThermoFrame decreases the thermal insulation value by approx. 55 % to up to 1.6 W/(m²·K), in comparison to an ALR F42.

Optional infills

We deliver the bottom door section as standard with PU infill and aluminium sheet cover, both sides Stucco-textured. Optionally, the door is available fully glazed without surcharge. Further information about the infill variations is available on page 50.

Bottom door section with PU infill (left)
or optionally with glazing (right)

Colour options page 47
Glazings page 48
Safety features in acc. with EN 13241-1, page 57.
Technical data page 82

Example door versions

Door width up to 4500 mm (example 4500 × 4500 mm)



ALR F42, ALR F42 Thermo,
ALR 67 Thermo
uniform field division



ALR F42, ALR F42 Thermo,
ALR 67 Thermo
wicket door in the centre

Door width up to 5500 mm (example 5500 × 4500 mm)



ALR F42, ALR F42 Thermo,
ALR 67 Thermo
uniform field division



ALR F42, ALR F42 Thermo,
ALR 67 Thermo
wicket door to the left

Door width over 5500 mm (example 7000 × 4500 mm)



ALR F42, ALR F42 Thermo,
ALR 67 Thermo
uniform field division
fully glazed



ALR F42, ALR F42 Thermo,
ALR 67 Thermo
wicket door in the centre
fully glazed

Clear passage width (LDB)
ALR F42, ALR F42 Thermo: 940 mm
ALR 67 Thermo: 905 mm

On request, uniform field division is also possible with wicket door.

The field division of the wicket door arrangement is also available in doors without wicket door.

For modernisation or when the matching appearance of the existing sectional doors must be ensured, the ALR F42 / ALR F42 Thermo is also available with 91-mm-wide rails.

Of course, individual arrangements of the glass and panel infills or full glazing are possible.

For full glazing from a door width of 5510 mm, the lower window sections are equipped on the inside with diagonal statics cross struts for better stability.

ALR F42 Glazing, ALR 67 Thermo Glazing

Aluminium doors with large glazing

Car showrooms
Thanks to large glazings made of real glass, the door becomes a display window, attracting potential customers.

Car showrooms
Bright, well-lit showrooms convey a sense of space and professionalism.

Warehouses
Large glazing provides workplaces with daylight.

Exclusively glazed aluminium doors

ALR F42 Glazing

1 The ideal display window door: continuous window sections with real glass offer an unimpeded view into showrooms. The window sections, all the exact same height, are produced without vertical rails for door widths of up to 3330 mm.

ALR 67 Thermo Glazing

2 For higher thermal insulation requirements, the ALR 67 Thermo Glazing is available with thermal break profiles, depth 67 mm.

Door type	ALR F42 Glazing	ALR 67 Thermo Glazing
Door size		
Max. width (mm)	5500	5500
Max. height (mm)	4000	4000
Thermal insulation EN 13241-1, Appendix B EN 12428 U-value in W/(m²·K) for a door surface 5000 × 5000 mm		
Standard single pane, laminated safety glass	6.1	–
Standard double pane, single-pane safety glass	–	3.0
With ThermoFrame	–	2.9
Optional climatic double pane, single-pane safety glass	2.7	1.8
With ThermoFrame	2.6	1.7

Matching side doors can be found on page 44

ALR F67 Thermo Glazing

The ALR 67 Thermo Glazing is especially suited for heated sales areas. The aluminium profiles have a thermal break and offer optimum thermal insulation while letting in maximum levels of natural light. The ALR 67 Thermo Glazing with optional climatic glazing and ThermoFrame decreases the thermal insulation value to a maximum of 1.7 W/(m²·K). This helps you save valuable energy.

ALR 67 Thermo Glazing with aluminium profiles with thermal break.

Colour options page 47
Glazings page 48
Safety features in acc. with EN 13241-1, page 57.
Technical data page 82

Example door versions

Door width up to 3330 mm
(Example 3300 × 3500 mm)



ALR F42 Glazing, ALR 67 Thermo Glazing

Door width over 3330 mm
(Example 4500 × 3500 mm)



ALR F42 Glazing, ALR 67 Thermo Glazing with vertical rail

For modernisation or when the matching appearance of the existing sectional doors must be ensured, the ALR F42 Glazing is also available with 91-mm-wide rails.

ALR F42 Vitraplan

Exclusively glazed aluminium doors

Exclusive door appearance
A clear overall appearance thanks to the offset glazing with a fascinating mix of mirroring and transparency.

reddot design award
winner 2010

Matching side doors
The combination of the sectional door and matching side door with offset glazing creates a harmonious overall appearance.

Designed facades
Permanent surface protection thanks to standard DURATEC glazing

Exclusively glazed aluminium doors

ALR F42 Vitraplan

1 **2** The surface-mounted, flush-fitting glazing fascinates with a mix of mirroring and transparency. The colours of the frame profiles are matched to the glazing colours in grey or brown.



1



2

Door type	ALR F42 Vitraplan
Door size	
Max. width (mm)	6000
Max. height (mm)	7500

Thermal insulation EN 13241-1, Appendix B EN 12428 U-value in W/(m²·K) for a door surface 5000 × 5000 mm	
Standard double pane	3.2
With ThermoFrame	3.2
Optional triple pane	3.1
With ThermoFrame	3.1

ALR F42 Vitraplan
For Sophisticated Architecture

The ALR F42 Vitraplan is especially elegant thanks to offset, flush-fitting glazing. The frame profile is concealed, so nothing detracts from the clear overall appearance.
Continuous glazing adds an eye-catching element to modern industrial structures and prestigious private buildings.

The door can be harmoniously integrated into the facade with glazings in brown and grey, as well as a dark frame profile colour that harmonises with the glass.

Synthetic pane, grey

Synthetic pane, brown

Colour options page 47
Glazings page 48
Safety features in acc. with EN 13241-1, page 57.
Technical data page 82

Example door versions

Door width up to 4500 mm
(Example 4500 × 4500 mm)



ALR F42 Vitraplan
uniform field division

Door width up to 5500 mm
(Example 5500 × 4500 mm)



ALR F42 Vitraplan
uniform field division

ALR F42

Aluminium doors for on-site cladding

On-site cladding with aluminium compound board

On-site cladding with timber panels

For flush-fitting cladding made of timber, metal and many other materials

On-site cladding with laminated timber boards

Aluminium doors for on-site cladding

ALR F42

The facade cladding door base consists of frame profiles with PU sandwich infill. The horizontal profiles are cladded. Optionally, we provide vertical fitting profiles to which the facade material can be attached simply and unseen.

You can design the on-site, flush-fitting facade cladding according to your wishes with timber, metal, ceramic, plastic and many other materials. Please observe the maximum weight per unit area of the on-site cladding. For further information, see the planning aid.

Door type	**ALR F42**
Door size	depending on weight of on-site cladding
Max. width (mm)	7000
Max. height (mm)	4500

Thermal insulation EN 13241-1, Appendix B EN 12428
U-value in W/(m²·K) for a door surface 5000 × 5000 mm

PU sandwich infill	2.6

Excerpt from the planning aid

Standard fitting in the opening

Standard version

1 Horizontal view
Door frame connection to the facade wall
2 Vertical view
Section transitions

Version with fitting profiles (red)

3 Horizontal view
Door frame connection to the facade wall
4 Vertical view
Section transitions

1



2



3



4



For detailed planning documents, please visit
http://www.hoermann.de/fileadmin/dokumentationen/anleitungen/garagen-sectionaltore/Fassadentor_Planungshilfen.pdf

Colour options page 47
Glazings page 48
Safety features in acc. with EN 13241-1, page 57.
Technical data page 82

Example door versions

Door width up to 4500 mm
(Example 4500 × 4500 mm)



ALR F42
uniform field division

Door width up to 5500 mm
(Example 5500 × 4500 mm)



ALR F42
uniform field division

Wicket doors with trip-free threshold

As a fully-fledged escape route

EUROPEAN PATENT
Only from Hörmann

World's first wicket door construction with thermal break, 67 mm depth

Trip-free passage

Wicket doors with trip-free thresholds pose less of a risk for persons stumbling and injuring themselves. Tool cars or trolleys can easily pass over the very flat stainless steel threshold with rounded edges.

The wicket door with trip-free threshold has many benefits:

- The garage door does not need to be opened for pedestrian traffic.
- It reduces the risk of tripping up and makes it easier to wheel things through.
- Power-driven doors feature a leading photocell VL 2 with two sensors which causes the door to reverse on encountering an obstruction well before contact is made.
- The wicket door contact ensures that the main door can only be opened when the wicket door is closed.

905 / 940 mm clear passage width as standard
Under certain circumstances, the wicket door with trip-free threshold, with its clear passage width of 905 mm (depth 67 mm) or 940 mm (depth 42 mm), fulfils the requirements of an escape door and for barrier-free construction.

As an escape door
Up to a door width of 5500 mm, Hörmann sectional doors with a wicket door with trip-free threshold fulfil the requirements of an escape door under certain circumstances.

As an unobstructed entrance
Under certain conditions, Hörmann sectional doors with a wicket door with trip-free threshold fulfil the requirements for accessibility in accordance with DIN EN 18040-1 and are certified by the IFT Rosenheim.

Freely selectable position
The wicket door can be positioned to the left, right or at the centre (except for the two outermost fields). The window sections above the wicket door have a clear view of 1025 mm as standard. All other fields of the door have the same width.

Take a look at the video at:
www.hoermann.com



The stainless steel threshold is 10 mm high at the centre and 5 mm at the edges. For doors with widths above 5510 mm, the threshold is approx. 13 mm high.


Wicket door construction for sectional doors with 42 mm depth


Wicket door construction with thermal break, for sectional doors with depth 67 mm


Wicket door to the left


Wicket door in the centre


Wicket door to the right

On request, doors with wicket door are also available with uniform field division and the wicket doors can be supplied in individual sizes or matching existing doors, even with threshold rails. We recommend the wicket door with threshold rail for inclining surfaces in the opening area.

Wicket doors with trip-free threshold

With high-quality equipment



Standard with concealed hinges

1

Overhead door closers
As standard, wicket doors are supplied with slide rail door closers incl. hold-open device (top figure).
An integrated door closer, including hold-open device (bottom figure), is optionally available for optimum protection and the best appearance (except for depth 67 mm).

2

Optional multiple-point locking
The wicket door is locked over the entire door height with one bolt and hook bolt per door section. The advantage: better stability and improved break-in-resistance (except for depth 67 mm).

3

Robust door catch
This prevents door-leaf drop and buckling.

Only Hörmann wicket doors with trip-free thresholds can be used without restriction in automatic operation thanks to the leading photocell VL 2

Flat wicket door frame
The all-round frame consists of a flat aluminium profile, harmoniously integrating the wicket door into the door.

Concealed hinges
For a uniform look, the wicket doors are equipped with concealed hinges as standard.

Finger trap protection
standard on the interior and exterior of wicket door frames (except for wicket door with depth 67 mm)

Optimally sealed
The adjustable threshold profile with flexible seal compensates for unevenness in the floor.

Adjustable double seals located in the transitions from the bottom edge of the door to the floor and the door leaf to the threshold optimally seal the bottom edge of the door and the wicket door opening.

Side doors
Matching the door

Side door NT 60

- 60 mm aluminium frame construction
- As standard with all-round seals made of long-lasting, weather-resistant EPDM
- Infill variations the same as for sectional doors with 42 mm depth
- Infill fixed by glazing beads

Side door NT 80 Thermo with thermal break *// NEW*

- 80 mm aluminium frame construction with thermal break
- As standard with all-round seals made of long-lasting, weather-resistant EPDM
- 42 mm panel infill with thermal break, fixed by glazing beads
- Infill variations the same as for sectional doors with 67 mm depth
- Glazing frame with thermal break with triple Duratec synthetic glazing

Fittings

- Mortice lock with profile cylinder
- Offset lever handle set with oval rose escutcheon, made of black plastic
- On request also available as lever / knob handle sets
- Optionally available in natural finish cast aluminium, polished stainless steel or brushed stainless steel

Optional equipment

- Stainless steel push bar 38-2, brushed, 1000 mm high, outside, additionally with stainless steel lever handle set, inside
- Overhead door closer with hold-open device
- Push bar for escape door, inside (panic lock required)
- Multiple-point locking

Side door NT 60 viewed from outside

Viewed from inside
with synthetic glazing

Viewed from inside with sections

Lever handle set as standard

Side door NT 80 Thermo viewed from outside



Viewed from inside
with triple synthetic glazing

Lever handle set as standard

Door leaf, frame and threshold
with thermal break

Steel side doors with thermal break

MZ Thermo Plus multi-purpose door

- 65-mm-thick door leaf with thermal break and PU rigid foam infill
- Aluminium block frame with thermal break and threshold with thermal break
- High thermal insulation with a U-value = 0.82 W/(m²·K)
- Optionally available in a WK 2 KSI Thermo version with 42-mm-thick door leaf

Additional information can be found in the Function doors for construction projects brochure.

Greater freedom to design with individual colour schemes

No surcharge for preferred colours for double-skinned steel sections with 42 mm and 67 mm depth

High-quality colour coating

The primer-coating of all industrial sectional doors from Hörmann is available in 10 preferred colours, as well as RAL and NCS, in many metallic colours as well as acc. to British Standard.*

The 2-component PUR coating on the exterior or on the exterior and interior and the coil coating procedure for double-skinned sections in preferred colours ensure high-quality, long-lasting colour. This maintains the attractive appearance of your door.

Dark colours should not be used for double-skinned steel doors and for doors with thermal break that are exposed to the sun, as possible section deflection may restrict the door's function (bi-metal effect).

The galvanized subframe and fittings are not factory-coated. Anodised profiles for the wicket door and glazing beads can be optionally coated on the outside. The frames for compound windows are black as standard. Door leaf reinforcements** and end caps are Grey white, RAL 9002, as standard.

Doors with double-skinned steel sections in any of the 10 preferred colours are supplied in Grey white, RAL 9002, on the inside (SPU F42 shown).

Door leaf reinforcements** and the end caps of the door sections on the inside of coloured doors are supplied in Grey white, RAL 9002, as standard. For doors with wicket doors, the frame of the wicket door on the inside consists of aluminium profiles in E6 / C0.

10 preferred colours

Traffic white	RAL 9016
Pure white	RAL 9010
Grey aluminium	RAL 9007
White aluminium	RAL 9006
Grey white	RAL 9002
Terra brown	RAL 8028
Anthracite grey	RAL 7016
Moss green	RAL 6005
Gentian blue	RAL 5010
Flame red	RAL 3000

The colours shown are subject to the limitations of the printing process and cannot be regarded as binding. Contact your Hörmann specialist dealer for advice regarding coloured doors. All colours based on RAL.

* With the exception of pearl-effect and fluorescent colours. Slight colour variations are permissible.
** Except for ALR F42 Vitraplan

Maximum scratch resistance and good thermal insulation

As standard for Hörmann sectional door glazing

Only from Hörmann

A permanently clear view

The new DURATEC glazing is available as standard and at no extra charge in all sectional doors with clear synthetic glazing.

With DURATEC synthetic glazing, Hörmann sectional doors retain their clear view permanently, even after multiple cleanings and heavy use.



DURATEC synthetic glazing
with maximum scratch resistance

Better protection against scratches caused by cleaning

A special surface coating, similar to that used on car headlights, protects the pane over the long-term from scratches and damage caused by cleaning.

Take a look at the video at:
www.hoermann.com

Sensitive, common synthetic glazing

Excellent thermal insulation as standard

Conventional double pane, 16 mm from other manufacturers

DURATEC double pane, 26 mm
Compared with conventional 16 mm glazing, the standard 26 mm double pane improves thermal insulation by up to **20 %**.



DURATEC triple pane, 26 mm
The optional triple glazing increases the effective thermal insulation by up to **35 %** in comparison to conventional 16-mm-thick glazing.



DURATEC triple pane, 51 mm
Thermal insulation is improved by up to **40 %** thanks to the optional triple glazing with a pane thickness of 51 mm, compared to a 16-mm-thick glazing.



DURATEC quadruple pane, 51 mm
In comparison to 16-mm glazing, the optional quadruple glazing increases the effective thermal insulation by up to **55 %**.



Climatic double pane, 26 mm
Using this type of pane helps to minimise heat transmission.
The improvement in thermal insulation is approx. **65 %**.



Glazings, infills

● = Possible	DURATEC glazing	SPU F42	SPU 67 Thermo	APU F42	APU F42 Thermo	APU 67 Thermo	ALR F42	ALR F42 Thermo	ALR 67 Thermo	ALR F42 Glazing	ALR 67 Thermo Glazing	ALR F42 Vitraplan
Aluminium glazing frame												
Synthetic panes												
Clear single pane	●	●		●			●					
Single pane, crystal structure		●		●			●					
Clear double pane	●	●		●	●		●	●				●
Double pane, crystal structure	●	●		●	●		●	●				●
Double pane, tinted brown, grey or white (opal)	●	●		●	●		●	●				
Clear triple pane	●	●	●	●	●	●	●	●	●			●
Triple pane, crystal structure	●	●	●	●	●	●	●	●	●			●
Triple pane, tinted in brown, grey or white (opal)	●	●	●	●	●	●	●	●	●			
Clear quadruple pane	●		●			●			●			
Quadruple pane, crystal structure	●		●			●			●			
Quadruple pane, tinted in brown, grey or white (opal)	●		●			●			●			
Polycarbonate panes												
Clear single pane	●	●		●			●					
Clear double pane	●	●		●	●		●	●				●
Real glass panes												
Clear single pane made of laminated safety glass		●		●			●			●		
Clear double pane, single pane safety glass		●	●	●	●	●	●	●	●	●	●	
Clear climatic double pane, single pane safety glass		●	●	●	●	●	●	●	●	●	●	
Infills												
Multiple-moulded pane (7 ×)		●		●	●		●	●				
Expanded mesh, stainless steel Ventilation cross section: 58 % of the infill surface		●		●			●					
Perforated steel sheet, stainless steel Ventilation cross section: 40 % of the infill surface		●		●			●					
PU-infill aluminium sheet cladding, anodised on both sides, smooth				●	●	●	●	●	●			
PU-infill, aluminium sheet cladding, Stucco-textured both sides				●	●	●	●	●	●			
Compound glazings												
Synthetic panes												
Clear double pane, synthetic frame	●	A,D,E	D									
Clear double pane, diecast frame	●	A	A									
Clear triple pane, synthetic frame	●		D									
Clear triple pane, diecast frame	●		A									
Clear quadruple pane, diecast frame	●		A									
Polycarbonate panes												
Clear double pane, diecast frame	●	A										

Aluminium glazing frame

Standard profile/Thermo profile

Standard profile / Thermo profile

Glazing frame:
Anodised E6 / C0 with / without thermal break
Clear view:
Depending on version
Rail extrusion:
52 mm, optional 91 mm (only for depth 42 mm)

Synthetic pane, clear



Synthetic pane, crystal structure

Synthetic pane, grey

Synthetic pane, brown

Synthetic pane, white (opal)

Multiple-moulded pane

Expanded mesh



perforated steel sheet

PU sandwich infill, smooth

PU sandwich infill, Stucco

Compound glazings



Type A

Type D



Type E

Type A

Glazing frame:
Plastic frame or diecast frame, black
Clear view:
635 × 245 mm
Door section height:
500, 625, 750 mm

Type D

Glazing frame:
Plastic frame, black
Clear view:
602 × 132 mm
Door section height:
500, 625, 750 mm

Type E

Glazing frame:
Black plastic frame
Clear view:
725 × 370 mm
Door section height:
625, 750 mm

Efficient thermal insulation

With a thermal break between frame and brickwork



Optimum thermal insulation with the SPU 67 Thermo



Good thermal insulation for SPU 42 Thermo

ThermoFrame optionally available for all industrial sectional doors

Well-insulated industrial sectional doors are essential in heated buildings. This is why Hörmann industrial sectional doors come with an optional ThermoFrame frame connection with a thermal break between the frame and brickwork. The lip seals on both door sides and the top section of the door provide additional insulation, reducing the heat transfer coefficient by up to 21 %.

- Thermal break between the frame and brickwork
- Additional seals for improved tightness
- Easy to fit along with the door frame
- Optimum corrosion-protection of the side frame
- **Up to 21 % better thermal insulation** in the SPU 67 industrial sectional door with a door surface of 3000 × 3000 mm

Only from Hörmann



Lintel fitting with ThermoFrame



Sideroom with ThermoFrame

SPU F42 door surface (mm)	**Without ThermoFrame** W/(m²·K)	**With ThermoFrame** W/(m²·K)	**Improvement** %
3000 × 3000	1.22	1.07	12.3
4000 × 4000	1.10	0.99	10.0
5000 × 5000	1.03	0.94	8.7
SPU 67 Thermo door surface (mm)			
3000 × 3000	0.81	0.64	21.0
4000 × 4000	0.69	0.56	18.8
5000 × 5000	0.62	0.51	17.7

Examples of track versions

Sound planning for old and new buildings

Track applications that fit precisely to the building

Whichever door type you have selected for your building: At Hörmann, you will find the a track application to match your door. Depending on the building architecture and requirement, you can choose between standard and low headroom track applications, low headroom track applications or inclined track applications.



Track application N
Normal track application

Track application H
High-lift track application

Track application L*
Low headroom track application

Track application V
Vertical track application



Track application ND*
With inclination

Track application HD*
With inclination

Track application LD*
With inclination

Track application VU
With low-mounted spring shaft

Please see the valid technical manual for all of the available track applications.

* Not for sectional door with 67 mm depth

Only from Hörmann

The low headroom track application

Operator and chain are directly on the door. An unsightly and potentially hazardous chain no longer dangles down. It pays to compare!



Hörmann's optimal arrangement

Competitors' arrangement

The best proof of quality: Advanced technology in every detail

1 Quiet door travel
Hinged roller holders made of galvanized steel with adjustable plastic rollers on ball-bearings ensure precise, quiet door travel.

Particularly service-friendly
If the frame is damaged in a collision, the **bolted tracks** can be exchanged easily and inexpensively.

2 Galvanized, articulated roller holder
The articulated roller holder reduces the headroom and protects the top door section from excessive bending when the door is open.

3 Strong-holding connections
Stable centre hinges made of galvanized steel connect the individual door sections precisely.
Edge profiling of the door sections has been designed so that the screws are held by multiple layers of sheet and are resistant to tearing out.

4 Upper frame end with connecting bracket
Permanently defined positions for the spring shaft bracket make it easier to fit the entire spring shaft.

Connection of spring shaft to cable drum
A separate feather key is not required; instead, a secure diecast connection increases functional safety and is easy to fit.
The shaft is galvanized, **the springs are coated.**

Flexible shaft coupling
Low variation in the axial alignment can be compensated by the flexible shaft coupling.

5 Pre-fabricated suspension
Ceiling suspension of the tracks is achieved through special anchors with slotted holes, made of galvanized steel. They are pre-fabricated as much as possible for the respective fitting situation.

SPU F42 shown

Safety features in accordance with European standard 13241-1

Doors must comply with the safety requirements of European standard 13241-1.
Have this confirmed by other manufacturers!

Hörmann products are tested and certified for:

Anti-fall safeguard

6 Reliable door guidance
The rollers are guided precisely in a **safety track** developed by Hörmann. This is why the door leaf cannot fall out during the turning phase or when parked near the ceiling.

7 Optimum counterbalance
The torsion spring assembly with grooved spring shaft ensures an optimum counterbalance. As a result, the door moves easily during the entire opening and closing phase.

8 Catch safety device (depending on equipment)
This load-dependent latch device is integrated in the load carrier for protection in case a cable or spring breaks. **European patent**

9 Spring safety device (depending on equipment)
Stops the torsion spring shaft if a spring breaks and securely holds the door in this position. **European patent**

Trap protection

10 Finger trap protection
The unique form of the door sections eliminates trap points on doors with a depth of 42 mm, both on the outside and inside.

11 Internally guided cables
The carrying cables are guided on the inside between the door leaf and frame. No protruding components. This virtually eliminates the risk of injuries. For doors with a low headroom track application, the load carrier consists of a carrying chain / carrying cable.

12 Side trap guards
The side frames are completely closed from top to bottom. This side trap guard is particularly safe.

13 Closing edge safety device
With the operators WA 400 and ITO 400, sensors monitor the bottom edge of the door and stop and reverse it in case of danger. The same effect is provided by the power limit of operators WA 300 and SupraMatic HT. A leading photocell or a light grille ensures particularly safe monitoring of the closing edge (for further information, see page 62). Obstructions are detected before they come into contact with the door.

Manually operated doors

As standard with pull rope or pull rod

Optional operation options



Optional: Hand pulley with rope or link steel chain



Optional: Chain hoist

Optional: Chain tensioner for easier operation

Securely locked as standard

Shootbolt
This can be secured with an on-site padlock as a secure night lock.

Only from Hörmann

Rotary latch
This door lock automatically locks itself through the latching disc. On request, it is also available for doors with VU and HU track applications (with low-mounted spring shaft).

Only from Hörmann

EUROPEAN PATENT

Floor locking
This enables frequently used doors to be released by foot. The automatic latch audibly engages when closed.

The door handle

Standard security

Lock operation from outside

With the handle set, the door lock can be ergonomically operated from outside. From inside, the lock is operated via T-handle and locking pin.
The profile cylinder can also be integrated into central locking systems.

Shootbolt

Rotary latch

Recessed handle set

Vertical door guidance, ideal for logistics applications, thanks to a flat design and flexible installation height (dock doors). You can operate two functions with the locking cylinder:
permanently unlocked door and automatic re-locking.

All parts on the inside are protected by cladding.

Shootbolt

Rotary latch

Compatible system solutions

For high functional door safety

Convenient door operation with BiSecur radio technology

Perfect interplay of door, operator and loading technology

Simple installation thanks to system components

Better with a system

Hörmann has developed its own operators and controls. This means the components have been optimally adjusted to work together, ensuring the door's functional safety.

The uniform operating concept and the 7-segment displays facilitate daily use. Fitting is also simplified thanks to uniform housing and cable sets. This way, all Hörmann products work together optimally and efficiently:

- Industrial doors
- Loading technology
- Operators
- Controls
- Accessories

Further information about the operators, controls and accessories can be found on pages 62 – 81.

Leading photocell VL 1

Optional for all power-driven sectional doors

No surcharge for WA 400 and ITO 400

Increased safety

Thanks to the non-contact automatic safety cut-out, persons and obstacles are quickly recognised without door contact. The door stops before contact and immediately travels upwards, virtually eliminating the risk of damage or injury.

Faster door travel

The leading photocell can close the door at a speed of up to 30 cm/s, reducing your energy costs due to shortened door opening times.

Lower inspection and maintenance costs

Industrial doors with non-contact door monitoring that have been approved for person safety purposes do not need to have their closing force approved. This means you save the extra costs for the additional inspection in accordance with ASR A1.7.

Closing edge safety device with optosensors or with leading photocell

All power-driven Hörmann industrial sectional doors with WA 400 and ITO 400 operators are equipped with a self-monitoring closing edge safety device with optosensors as standard. You can also select the leading photocell VL 1 for non-contact door monitoring of the closing edge without a surcharge. This solution offers you increased safety, faster door action and lower inspection and maintenance costs.

Only from Hörmann

EUROPEAN PATENT

Leading photocell VL 1

Leading photocell VL 2

Leading photocells

Using the leading photocells VL 1 and VL 2 means increasing the safety of Hörmann industrial sectional doors. The sensors monitor the bottom edge of the sectional door. Obstacles or persons are quickly recognised and the sectional door reverses before contact is made. Another benefit is the faster door travel speed.

The non-contact, automatic safety cut-out protects people and property

The crash protection at the sides prevents the swivel arm from being damaged when the door is closed.

Light grille
Integrated into the frame

Light Grille ELG

The light grille integrated in the frame recognises persons and obstacles without making contact, virtually eliminating the risk of damage or injury.
A closing edge safety device with optosensors or additional photocells is not required. Fitting the light grille in the frame means exceptional protection against damage or accidental readjustments.

For controls
A / B 445, A / B 460, B 460 FU

Not approved for sectional doors with wicket door with trip-free threshold.

- **Maximum safety**
  Persons and obstacles are effectively recognised thanks to the cross-beam sensors.
- **Increased personal protection**
  Up to a height of 500 mm (above FFL) the sensors are arranged with an especially tight spacing.
- **Improved energy efficiency**
  The door can be shut at a speed of up to 45 cm/s (with operator WA 400 FU and control 460 FU, depending on track application and size).
- **Protection against damage**
  The light grille is integrated in the frame for optimum protection.
- **Easy fitting**
  The mounting brackets securely fasten the light grille with optimum alignment in the frame.
- **Can be retrofitted**
  Existing doors with closing edge safety device with optosensors can be easily retrofitted with the HLG light grille.
- **Lower inspection and maintenance costs**
  Inspection of the closing force in accordance with ASR A1.7 is not necessary.

Other photocells and light grilles

Photocell RL 50 / RL 300
Reflection photocell with transmitter / receiver unit and reflector.
The photocell is tested by the control prior to each closing cycle.
Connected via a system cable (RL 50, length 2 m) or a 2-wire cable (RL 300, length 10 m).
Dimensions:
68 × 97 × 33 mm (W × H × D)
Protection category: IP 65
Reflector range up to 8 m (standard):
30 × 60 mm (W × H)
Reflector range up 12 m (not shown):
80 mm diameter
(optionally with anti-fog coating)

One-way photocell EL 51
Photocell with separate transmitter and receiver
The photocell is tested by the control prior to each closing cycle.
Connected via a system cable,
Max. 8 m range,
Dimensions with fitting bracket:
60 × 165 × 43 mm (W × H × D)
Protection category: IP 65

Light grille ELG
The light grille monitors the entire closing zone of the door up to a height of 2500 mm.
The ELG 1 light grille can be easily integrated in the STL post set made of weather-resistant anodised aluminium.

Voltage supply: 24 V DC,
Power consumption: 100 mA each,
Range: 0 to 12 m,
Protection category: IP 65
Sun suppression: 150,000 lux,
Operating temperature: –25 °C to +55 °C,
Resolution: 60 mm crossed,
Light source: LED infrared,
Transmitter lead length: 10 m,
Receiver lead length: 5 m,
Height: ELG 1 = 1380 mm, ELG 2 = 2460 mm

Shaft operator WA 300 S4

With standard soft start and soft stop

Soft start / stop
For gentle and quiet door travel, thereby sustainably increasing the service life of the door system.

Lower investments, lower consumption
The WA 300 S4 costs approx. 30 % less than a 3-phase current operator, and daily power consumption is reduced by up to 75 %.

Simple, fast fitting and start-up
since many components have already been pre-assembled and no closing edge safety devices or cable slack switches have to be fitted.

For further information, please see the fitting data or contact your Hörmann partner.

Advantages at a glance

Particularly easy to fit and maintain thanks to its power limit as standard
For doors without wicket doors, installing items such as closing edge safety devices or cable slack switches on the door is not required. This reduces costs and the risk of repair and services.

Safe “Close” travel with reduced speed
All “Open” travel as well as “Close” travel above a 2500 mm opening height takes place at a speed of approx. 19 cm/s. With an opening height below 2500 mm, “Close” travel must be set to approx. 10 cm/s for safety reasons. This restriction does not apply to optional leading photocells or closing edge safety devices, meaning the door opens and closes at approx. 19 cm/s.

Integrated control with push button DTH R
Operator WA 300 S4 can also optionally be supplied with external control 360 (prepared for traffic control).

Door sizes
Max. door width 6000 mm
Max. door height 4500 mm

For max. 150 door cycles per day
or up to 100 parking spaces in collective garages

Diagonal fitting variant

Vertical fitting variant

Only from Hörmann

EUROPEAN PATENT

As standard with WA 300 S4

- **Soft start and soft stop for gentle and quiet door travel**
- **Power limit in “Open”/“Close” directions**
- **Integrated control with push button DTH R**
- **Small side room of only 200 mm**
- **No installations or cabling required on the door***
- **No cable slack switch required**
- **Only approx. 1 watt power consumption in stand-by mode (if no other electrical accessories are connected)**

* Except for doors with wicket doors

Maintenance release directly on the operator

During the statutory annual door inspection, it is not necessary for the operator to be removed from the door shaft, which saves time and money. The maintenance release can be converted to a secured release at any time.

Optional push button control 300 U

Push button control 300 U (in the image above) forms a compact unit with dock leveller controls 420 S and 420 T. Combined with a dock leveller control with the new energy-saver function, this reduces energy consumption. Push button control 300 U is also optionally available with integrated main switch (not shown).

On request with integrated option relay:

- “Open” limit switch reporting for dock leveller release
- No magnetic switch required on the door
- Minimum cabling required

Optional releases

Secured release on inside
For the convenient release of the operator from the floor (European patent)

Secured release from outside ASE
To unlatch the door from the outside (required for buildings without a second entrance). Lockable diecast housing with profile half cylinder.
Dimensions:
83 × 133 × 50 mm (W × H × D)

Emergency operation
For manual operation of higher doors from 3000 mm (see figure on page 69)

Emergency battery
With this emergency power in an external housing, you can bypass network power failures for up to 18 hours and max. 5 door cycles (dependent on the temperature and charge level). The emergency battery recharges itself during normal operation. For control 360, the emergency supply takes place via an optional UPS system (see page 73).

Shaft operator WA 400, WA 400 M

Strong and robust

Operator to flange
WA 400

This patented flange version is simple and quick to fit to the spring shaft and requires considerably less sideroom than the direct drive solutions from other manufacturers.

Can be combined with controls
A / B 445, A / B 460, B 460 FU

Standard fitting position: horizontal, alternatively vertical, shown with an optional emergency hand chain

Operator with chain box
WA 400

We recommend the WA 400 operator with chain box for all types of doors up to a height of 7500 mm if there is only sideroom of up to 200 mm. For applications L and LD an operator WA 400 with chain box is required. Due to the indirect transmission of forces, the door is subjected to minimum wear and friction.

Can be combined with controls
A / B 445, A / B 460, B 460 FU

Standard fitting position vertical, shown with an optional emergency hand chain

Operator for central mounting
WA 400 M

This version is mounted centrally on the spring shaft, as a result, no additional sideroom is necessary.
Note the required headroom!
The WA 400 M includes a secured release as a standard feature and is suitable for virtually any track application.

Can be combined with controls
A / B 445, A / B 460, B 460 FU

Central mounting, when sideroom is lacking.

Only from Hörmann

With all 3-phase current versions:

- **Exceptionally smooth running**
- **Long on-time**
- **Fast door travel**
- **Also as an FU version**

Standard maintenance release

During the statutory annual door inspection, it is not necessary for the operator to be removed from the door shaft, which saves time and money. The maintenance release can be converted to a secured release at any time.

Optional emergency operation for maintenance release

Emergency crank handle
The low-cost option is available in two versions, as a fixed crank handle or jointed emergency crank handle. Retrofitting with an emergency hand chain is possible.

Emergency hand chain
Through a combination of the emergency hand chain and the optional secured release, the door can be released or operated from the floor.

Emergency operation
Recommended for doors over 3000 mm and fire station doors. A secured release is required.

Meets the requirements of fire service directive EN 14092.

Optional releases

Secured release on inside
(As standard with WA 400 M)
For the convenient release of the operator from the ground (European patent)

Secured release from outside ASE
To unlatch the door from the outside (required for buildings without a second entrance). Lockable diecast housing with profile half cylinder.
Dimensions:
83 × 133 × 50 mm (W × H × D)

Operator SupraMatic HT ITO 400

The space-saving operator

Chain drive with boom guidance ITO 400

- No additional sideroom required
- Emergency release via bowden cable on the slide carriage
- Emergency release from the outside possible
- IP 65 (jet-water protected)
- For normal track application (N, ND) and low headroom track application (L, LD)
- Max. door height 4500 mm
- Also available as FU version
- For doors with wicket doors on request

Can be combined with controls A / B 445, A / B 460 and B 460 FU



Operator SupraMatic HT

- Suitable for up to 100 parking spaces
- Pull and push force 1000 N (brief peak force 1200 N)
- With integrated control electronics including double 7-segment display for simple adjustment of the operator functions directly on the operator
- Optional external control 360 for connecting traffic control, warning lights or additional prints
- Soft start and stop for gentle, quiet door travel
- Patented door locking in the operator boom with emergency release from inside
- Connecting lead with EEC plug, second suspension
- For doors with a spring safety device
- SupraMatic HT: max. width 6750 mm (7000 mm on request), max. height 3000 mm
- For normal track application (N) and low headroom track application (L)
- For doors with wicket doors, ALR F42 Glazing and real glass on request
- Not for sectional doors with a depth of 67 mm

Tightly locked and protected against forced opening

Thanks to a break-in-resistant arrestor kit

Anti-lift kit as standard up to 5 m

It is especially important for industrial doors to be reliably break-in-resistant to protect your goods and machines. At Hörmann, all industrial sectional doors up to 5 m height equipped with operators WA 300 S4 / WA 400 are supplied with a break-in-resistant arrestor kit as standard. This mechanical protection reliably prevents the door from being forcefully pushed open, even in case of a power failure.

Industrial sectional doors over 5 m high are break-in resistant due to their heavy weight.

In sectional doors with rail-guided operators, self-locking gearboxes (ITO 400) or patented locking in the operator boom (SupraMatic HT) protect against forced opening.

Increased security for night doors

Hörmann offers optional locking systems for special protection. In power-driven doors, an additional mechanical shootbolt can be installed (see the figure on page 58). Because it is equipped with a shoot-bolt switch, the operator cannot be started if the door is locked.

The locking hook of the arrestor kit automatically latches if the door is forced upwards.

Controls

Compatible system solutions

	Internal control WA 300 S4	External control 360	Impulse control A / B 445	Comfort control A / B 460	FU control B 460 FU
Operators					
WA 300 S4	●	○			
WA 400			●	●	
WA 400 FU					●
Functions / features					
Control and operator can be mounted separately		●	●	●	●
Adjustments made conveniently directly on the control		●	●	●	●
Soft start and soft stop for gentle and quiet door travel	●	●			●
Adjustable high-speed opening and closing (depending on tracks)	● [1]	● [1]			●
Power limit in Open and Close directions	● [2]	● [2]	●	●	●
Integrated Open / Stop / Close operation	●	●	●	●	●
Second opening height with additional button on the housing cover	○ [3]	●		●	●
Menu reading from outside with a double 7-segment display (maintenance, cycle and operating hours counters as well as error analysis)		●	●	●	●
Collective malfunction signalling with on-site individual display (acoustic, visual, or e.g. via mobile phone).		●	○	○	○
Extension possible with external radio receiver	●	●	●	●	●
Inquiry of the door position	○ [4]	○ [5]	○ [5]	○ [5]	○ [5]
Automatic timer [6]	●	●		●	●
Traffic control [6]		○		○	○
Connecting terminals for additional command units	●	●	●	●	●
Power supply	230 V	230 V	400 / 230 V	400 / 230 V	230 V
Connection cable with CEE plug [7] (Protection category IP 44)	●	●	●	●	●
Main switch integrated into control housing	○ [8]	○	○	○	○
Protection category IP 65 (jet-water protected) for controls and door leaf components	●	●	●	●	●

● = as standard
○ = with corresponding equipment possibly with additional control

[1] In the Close direction during operation without SKS / VL (during operation with SKS / VL, the door generally travels at high speed in the Close direction)
[2] In accordance with EN 12453
[3] Possible in combination with UAP 300 and DTH I or DTH IM
[4] in combination with ESEi BS, HS 5 BS or Hörmann app (Gateway required)
[5] in combination with HET-E2 24 BS, HS 5 BS or Hörmann app (Gateway required) and end-of-travel feedback
[6] Only in combination with an activating kit for warning light and photocell or light grille or leading photocell VL 1 / VL 2
[7] For controls with integrated main switch the connecting cable is omitted
[8] External main switch possible or through operating unit 300 U with integrated main switch

Optional:
Profile half cylinder
For all external controls

Optional:
Main switch
For all external controls

UPS system
For bridging power failures of up to 4 hours, safety devices, warning lights, etc., remain functional, LED status display, automatic battery test, surge filter,
Dimensions: 560 × 235 × 260 mm (W × H × D),
Protection category: IP 20

For controls
360, B 445, B 460

Optional:
Key switch post STI 1
For installing a maximum of 2 controls with additional housing.
Colour: White aluminium, RAL 9006
Dimensions: 200 × 60 mm,
height 1660 mm

Accessories

Radio control, receivers

Only from Hörmann

Hörmann BiSecur (BS)

The modern radio system for industrial door operators

The bi-directional BiSecur radio system is based on future-oriented technology for the convenient and secure operation of industrial doors. The extremely secure BiSecur encryption protocol makes sure that no-one can copy your radio signal. It was tested and certified by security experts at Bochum University.

Your advantages

- **128-bit encryption with the same high security level as in online banking**
- **Interference-resistant radio signal with a stable range**
- **Convenient inquiry of the door position***
- **Backwards compatible, i.e. radio receivers with the frequency 868 MHz (2005 to June 2012) can also be operated with BiSecur control elements**

5-button hand transmitter
HS 5 BS
With additional button for querying the door position*, black or white textured surface, with chrome caps

5-button hand transmitter
HS 5 BS
With additional button for querying the door position*, black textured surface, with chrome caps

4-button hand transmitter
HS 4 BS
High-gloss black, with chrome caps

1-button hand transmitter
HS 1 BS
High-gloss black, with chrome caps

4-button security hand transmitter
HSS 4 BS
Additional function: copy protection for hand transmitter coding, with chrome caps

2-button hand transmitter
HSE 2 BS
High-gloss black or white, with chrome caps

2-button hand transmitter
HSE 2 BS
Black textured surface with chrome or plastic caps

1-button hand transmitter
HSE 1 BS
High-gloss black, with chrome caps

* With WA 300 S4 with optional bi-directional receiver ESEi BS, for all other operators with optional bi-directional receiver HET-E2 24 BS and end-of-travel feedback.

Industrial hand transmitter
HSI BS
To control up to 1000 doors, with a display and extra-large quick selection buttons for easier operation with work gloves, transferring of hand transmitter coding to other devices possible

Radio code switch
FCT 3 BS
With illuminated buttons
3 function codes

Radio code switch
FCT 10 BS
With illuminated buttons and protective cover, 10 function codes

BiSecur

Radio finger-scan
FFL 12 BS
2 function codes
and up to 12 fingerprints

1-channel relay receiver
HER 1 BS
With volt-free relay output with status query ***NEW***

2-channel relay receiver
HER 2 BS
With 2 volt-free relay outputs with status query and external antenna ***NEW***

2-channel relay receiver
HET-E2 24 BS
With 2 volt-free relay outputs for choosing the direction, a 2-pin input for volt-free Open and Close limit switch reporting (for querying the door position)

BiSecur

4-channel relay receiver
HER 4 BS
With 4 volt-free relay outputs with status query ***NEW***

3-channel receiver
HEI 3 BS
For controlling 3 functions

Bi-directional receiver
ESEi BS
For querying door position

BiSecur

Accessories
Push buttons

Push button DTH R
For separate control of both operational directions, with separate stop button and protection category: IP 65
Dimensions: 90 × 160 × 55 mm (W × H × D)

For controls
360, A / B 445, A / B 460, B 460 FU and integrated control WA 300 S4

Push button DTH RM
For separate control of both operational directions, with separate stop button and with miniature lock: Operator is deactivated. The operator can no longer be actuated (2 keys included in the scope of delivery).
Protection category: IP 65
Dimensions:
90 × 160 × 55 mm (W × H × D)

For controls
360, A / B 445, A / B 460, B 460 FU and integrated control WA 300 S4

Push button DTH I
To move the door into the Open / Close positions, separate stop button to stop door travel, 1/2-open button to open the door up to the programmed intermediate travel limit.
Protection category: IP 65
Dimensions:
90 × 160 × 55 mm (W × H × D)

For controls
360, A / B 460, B 460 FU and integrated control WA 300 S4
(only in combination with UAP 1)

Push button DTH IM
To move the door into the Open / Close positions, separate stop button to stop door travel, 1/2-open button to open the door up to the programmed intermediate travel limit, with miniature lock: operator is deactivated. The operator can no longer be actuated (2 keys included in the scope of delivery).
Protection category: IP 65
Dimensions:
90 × 160 × 55 mm (W × H × D)

For controls
360, A / B 460, B 460 FU and integrated control WA 300 S4
(only in combination with UAP 1)

Push button DT 02
Open or close via a command button, separate stop button.
Dimensions:
65 × 112 × 68 mm (W × H × D)
Protection category: IP 65

For controls
A / B 445, A / B 460 and B 460 FU

Push button DT 03
For separate control of both operational directions, with separate stop button.
Dimensions:
66 × 155 × 85 mm (W × H × D)
Protection category: IP 65

For controls
A / B 445, A / B 460 and B 460 FU

Push button DT 04
For separate control of both operational directions, with separate stop button, full or partial door opening (via separate button),
Dimensions:
69 × 185 × 91 mm (W × H × D)
Protection category: IP 65

For controls
A / B 460 and B 460 FU

Push button DTN A 30
For separate control of both operational directions. The stop button is a push-to-lock button which, once pressed, stays depressed in order to prevent unauthorised operation. Subsequent operation is then only possible once the stop button has been unlocked with a key (2 keys included in the scope of delivery).
Dimensions:
66 × 145 × 85 mm (W × H × D)
Protection category: IP 65

For controls
A / B 445, A / B 460 and B 460 FU

Accessories

Push buttons, key switches, key switch posts

Push button DTP 02
Open or close via a command button, separate stop button and operation control light for control voltage, lockable with profile half cylinder (available as an accessory),
Dimensions:
86 × 260 × 85 mm (W × H × D)
Protection category: IP 44

For controls
A / B 445, A / B 460 and B 460 FU

Push button DTP 03
For separate control of both operational directions, separate stop button and operation control light for control voltage, lockable with profile half cylinder (available as an accessory).
Dimensions:
68 × 290 × 74 mm (W × H × D)
Protection category: IP 44

For controls
A / B 445, A / B 460 and B 460 FU

Emergency-off button DTN 10
To quickly immobilise the door, push-to-lock button (mushroom button), surface-mounted.
Dimensions:
93 × 93 × 95 mm (W × H × D)
Protection category: IP 65

For controls
A / B 445, A / B 460 and B 460 FU

Emergency-off button DTNG 10
To quickly immobilise the door, oversize push-to-lock mushroom button, surface-mounted.
Dimensions:
93 × 93 × 95 mm (W × H × D)
Protection category: IP 65

For controls
A / B 445, A / B 460 and B 460 FU

The lockable function serves to isolate the control voltage and immobilises the command units. Profile half cylinders are not included in the scope of delivery for the push buttons.

Key switch ESU 30 with 3 keys
Recessed version, Impulse or Open/Close function selectable.
Dimensions of switch box:
60 mm (d), 58 mm (D)
Dimensions of cover:
90 × 100 mm (W × H),
Wall recess:
65 mm (d), 60 mm (D)
Protection category: IP 54

Surface-mounted version ESA 30 (not shown)
Dimensions:
73 × 73 × 50 mm (W × H × D)

Key switch STUP 30 with 3 keys
Recessed version, Impulse or Open/Close function selectable.
Dimensions of switch box:
60 mm (d), 58 mm (D)
Dimensions of cover:
80 × 110 mm (W × H)
Wall recess:
65 mm (d), 60 mm (D)
Protection category: IP 54

Surface-mounted version STAP 30 (not shown)
Dimensions:
80 × 110 × 68 mm (W × H × D)

ZT 2 pull switch with cord
Impulse generation to open or close the door
Dimensions:
60 × 90 × 55 mm (W × H × D)
Pull cord length: 3.2 m
Protection category: IP 65

Cantilever arm KA1 (not shown)
Extension 1680 – 3080 mm.
Can be used with ZT 2

Key switch post STS 1
With adapter for fitting TTR 100, FCT 10 b, CTR 1b / CTR 3b or STUP. The command units must be ordered separately. The post is anodised aluminium (natural finish). Top and bottom end of post in Slate grey, RAL 7015.
Dimensions:
300 mm (d), 1250 mm (H)
Protection category: IP 44

Version with fitted key switch STUP 30 (accessory)

Accessories
Code switches

Code switch CTR 1b, CTR 3b
The code switches CTR 1b and CTR 3b offer a high level of security against unauthorised opening. Simply enter your personal code; a key is no longer required.
The CTR 3b comfort version allows you to open a second door and switch on the outside lighting or operate a door in your choice of direction.

Dimensions:
80 × 110 × 17 mm (W × H × D),
Decoder housing:
140 × 130 × 50 mm (W × H × D)
Keypad protection category: IP 65
Decoder housing protection category: IP 54
Switching capacity: 2.5 A / 30 V DC
500 W / 250 V AC

Code switch CTV 1, CTV 3
The code switches are especially robust and protected against vandalism. To operate, you enter your own personal code – no key is needed.
With the CTV 3 comfort version, you can open a second door and also switch on the outside lights or operate a door in the chosen direction.

Dimensions:
75 × 75 × 13 mm (W × H × D),
Decoder housing:
140 × 130 × 50 mm (W × H × D)
Keypad protection category: IP 65
Decoder housing protection category: IP 54
Switching capacity: 2.5 A / 30 V DC
500 W / 250V AC

Finger-scan FL 12, FL 100
A fingerprint is enough to securely and conveniently open your industrial sectional door. The finger-scan is available in two versions, as an FL 12 or FL 100 to store 12 or 100 fingerprints, respectively.

Dimensions:
80 × 110 × 39 mm (W × H × D)
Decoder housing:
70 × 275 × 50 mm (W × H × D)
Reader protection category: IP 65
Decoder housing protection category: IP 56
Switching capacity: 2.0 A / 30 V DC

Transponder key switch TTR 100, TTR 1000
The convenient solution when several persons require access to the building. You simply hold the transponder key with your personal security code approx. 2 cm in front of the reader. A non-contact system! A major benefit in the dark. 2 keys are included. Suitable for max. 100 transponder keys (TTR 100) or 1000 transponder keys (TTR 1000).

Dimensions:
80 × 110 × 17 mm (W × H × D),
Decoder housing:
140 × 130 × 50 mm (W × H × D)
Transponder pad protection category: IP 65
Decoder housing protection category: IP 54
Switching capacity: 2.5 A / 30 V DC
500 W / 250 V AC

Accessories

Activating kits, LED warning lights

Warning lights with bright, long-lasting LEDs

Multi-function circuit board for fitting in an existing housing or optionally in a separate extension housing (fig.)
Limit switch reporting, momentary impulse, collective malfunction signalling, extension unit for controls 360, A / B 445, A / B 460, B 460 FU

Dimensions of additional housing:
202 × 164 × 130 mm (W × H × D)
Protection category: IP 65
A circuit board can be optionally mounted in the control.

Digital weekly timer in a separate additional housing
The timer can switch command units on and off via a volt-free contact. Extension unit for controls A / B 460, B 460 FU, 360 (no additional housing, for fitting in an existing housing), switching capacity: 230 V AC: 2.5 A/500 W, Can be switched over to summer / winter time, manual switching: automatic operation, switching preselection permanently ON / OFF.

Dimensions of additional housing:
202 × 164 × 130 mm (W × H × D)
Protection category: IP 65

Summer / winter activating kit in an additional housing
Function for full opening of door and individually programmable intermediate travel limit, extension unit for controls A / B 460, B 460 FU.

Dimensions of additional housing:
202 × 164 × 130 mm (W × H × D)
Protection category: IP 65

Activating kit for warning lights for fitting in an existing housing or optionally in a separate extension housing (fig.), incl. 2 yellow warning lights
Extension unit for controls 360, A / B 445, A / B 460, B 460 FU.
The activating kit for warning lights serves as a visual indicator while the door is moving (weekly timer, optionally for 360, A / B 460, B 460 FU).
Applications: approach warning (for 360, A / B 445, A / B 460, B 460 FU), automatic timer (for 360, A / B 460, B 460 FU). After the set hold-open phase has elapsed (0 – 480 s), the warning lights flash during the set pre-warning phase (0 – 70 s).
Traffic light dimensions: 180 × 250 × 290 mm (W × H × D)
Dimensions of additional housing: 202 × 164 × 130 mm (W × H × D),
Contact load: 250 V AC : 2.5 A / 500 W,
Protection category: IP 65

Traffic control in separate additional housing (A / B 460, B 460 FU) or for fitting in an existing housing (360) incl. 2 red / green warning lights
Extension unit for controls 360, A / B 460, B 460 FU
The activating kit for warning lights serves as a visual indicator for regulating the entrance and exit (optional weekly timer).
Duration of the green phase: adjustable 0 – 480 s
Duration of the clearance phase adjustable 0 – 70 s
Traffic light dimensions: 180 × 410 × 290 mm (W × H × D)
Dimensions of additional housing: 202 × 164 × 130 mm (W × H × D),
Contact load: 250 V AC : 2.5 A / 500 W,
Protection category: IP 65

Accessories
Activating kits

DI 1 induction loop
in a separate additional housing
Suitable for one induction loop. The detector has a normally open contact and a change-over contact.

DI 2 induction loop (not shown)
in a separate additional housing
Suitable for two separate induction loops.
The detector has two volt-free normally open contacts.
Can be set for impulse or permanent contact,
directional recognition possible
Dimensions of additional housing:
202 × 164 × 130 mm (W × H × D)
Switching capacity:
DI 1: low voltage 2 A, 125 V A / 60 W,
DI 2: 250 V AC, 4 A, 1000 VA,
(resistivity AC),
Supplied without loop cable

Loop cable for induction loop
Roll of 50 m,
Cable designation: SIAF,
Cross section: 1.5 mm²,
Colour: brown

Radar movement detector RBM 2
For “Open door” impulse with directional recognition
Max. fitting height: 6 m
Dimensions:
155 × 132 × 58 mm (W × H × D)
Contact load:
24 AC/DC , 1 A (resistivity),
Protection category: IP 65

Optional remote control for radar movement detector

UAP 1-300
For WA 300 S4
For impulse selection, partial opening function, limit switch reporting and activating kit for warning light with 2 m system cable,
Protection category: IP 65
Max. switching capacity:
30 V DC / 2.5 A (resistivity),
250 V AC / 500 W (resistivity),
Dimensions:
110 × 45 × 40 mm (W × H × D)

HOR 1-300
For WA 300 S4
To control limit switch reporting or warning lights
with 2 m connecting lead,
Protection category: IP 44
Max. switching capacity:
30 V DC / 2.5 A (resistivity),
250 V AC / 500 W (resistivity),
Dimensions:
110 × 45 × 40 mm (W × H × D)

Also optionally available for integration into
the push button control 300 U (not shown) ***// NEW***

Hörmann is your partner for special solutions

Special control construction

Hörmann offers you a complete and individual control concept from a single source: From the integration of the Hörmann special control into your control concept via a complete central control for all functional processes, up to a PC-based visualisation of all door and loading components.

Individual in-house project development

Modular solutions, compatible with the Hörmann operator technology

Controlled processes through visualisation on a control panel or web application



More information can be found in the Special control systems brochure.

Performance characteristics according to EN 13241-1

Door types	SPU F42	SPU 67 Thermo	APU F42	APU F42 Thermo	APU 67 Thermo	ALR F42	ALR F42 Thermo	ALR 67 Thermo
Wind load	Class according to EN 12424							
Up to door widths of 8000 mm	3 [1]	3 [1]	3 [1]	3 [1]	3 [1]	3 [1]	3 [1]	3 [1]
From door widths of 8000 mm		2			2			2
Water tightness	Class according to EN 12425							
	3 (70 Pa)	3 (70 Pa)	3 (70 Pa)	3 (70 Pa)	3 (70 Pa)	3 (70 Pa)	3 (70 Pa)	3 (70 Pa)
Air permeability	Class according to EN 12426							
Sectional door without wicket door	2	2	2	2	2	2	2	2
Sectional door with wicket door	1	1	1	1	1	1	1	1
Acoustic insulation [2]	R [db] according to EN ISO 717-1							
Sectional door without wicket door	25	25	23	23	23	23	23	23
With real glass panes						30	30	30
Sectional door with wicket door	24	24	22	22	22	22	22	22
Thermal insulation Sectional doors without wicket door	U-value = W/(m²·K) according to EN 13241, Appendix B, for a door size from 5000 × 5000 mm							
Fitted door	1.0	0.62						
With ThermoFrame	0.94	0.51						
Synthetic double panes			3.4	2.9		3.6	3.0	
With ThermoFrame			3.3	2.8		3.6	3.0	
Synthetic triple panes			3.0	2.5	2.1	3.2	2.6	2.2
With ThermoFrame			2.9	2.4	2.0	3.1	2.5	2.1
Synthetic quadruple pane					1.8			1.9
With ThermoFrame					1.7			1.8
Climatic double pane			2.5	2.0	1.6	2.7	2.1	1.7
With ThermoFrame			2.4	1.9	1.5	2.6	2.0	1.6
Double real glass pane			3.4	2.9	2.6	3.6	3.0	2.7
With ThermoFrame			3.3	2.8	2.5	3.6	3.0	2.6
Single real glass pane								
With ThermoFrame								
Thermal insulation Sectional doors with wicket door	U-value = W/(m²·K) according to EN 13241, Appendix B, for a door size from 5000 × 5000 mm							
Fitted door	1.2	0.82						
With ThermoFrame	1.2	0.75						
Synthetic double panes			3.6	3.1		3.8	3.2	
With ThermoFrame			3.6	3.1		3.8	3.2	
Synthetic triple panes			3.2	2.7	2.3	3.4	2.8	2.4
With ThermoFrame			3.1	2.6	2.2	3.4	2.8	2.3
Synthetic quadruple pane					2.0			2.1
With ThermoFrame					1.9			2.1

[1] With wicket door and door wider than 4000 mm class 2
[2] For combined infills the weaker is the most critical (e.g. APU, SPU with glazing frame).

Side doors	NT 60 for SPU	NT 60 for APU	NT 60 for ALR	NT 60 for ALR Vitraplan	NT 80 Thermo f or SPU	NT 80 Thermo for APU	NT 80 Thermo for ALR
Wind load Class according to EN 12424	3C	3C	3C	3C	4C	4C	4C
Air permeability Class according to EN 12426	3	3	3	3	3	3	3
Watertightness under heavy rain Unprotected, opening outwards	1A	1A	1A	1A	1A	1A	1A
Thermal insulation U-value = W/(m²·K) according to EN 13241, Appendix B, for a door size of 1250 × 2200 mm	2.9	4.2	4.7	4.7	1.6	2.2	2.4

	ALR F42 Glazing	ALR 67 Thermo Glazing	ALR F42 Vitraplan
	3	3 2	3
	3 (70 Pa)	3 (70 Pa)	3 (70 Pa)
	2	2	2
	30	30	23
			3.2 3.2
			3.1 3.1
	2.7 2.6	1.8 1.7	
	3.8 3.8	3.0 2.9	
	6.1 6.1		

Glazings/infills	Ug value W/(m²·K)	τ_v value	g-value
Synthetic panes			
Single pane, 3 mm			
Clear		0.88	
Crystal structure		0.84	
Double pane, 26 mm			
Clear	2.6	0.77	0.74
Crystal structure	2.6	0.77	0.74
Grey tinted	2.6	0.03	0.28
Brown tinted	2.6	0.03	0.25
White tinted (opal)	2.6	0.69	0.69
Triple pane, 26 mm			
Clear	1.9	0.68	0.67
Crystal structure	1.9	0.68	0.67
Grey tinted	1.9	0.03	0.25
Brown tinted	1.9	0.03	0.23
White tinted (opal)	1.9	0.61	0.63
Triple pane, 51 mm			
Clear	1.6	0.68	0.67
Crystal structure	1.6	0.68	0.67
Grey tinted	1.6	0.03	0.25
Brown tinted	1.6	0.03	0.22
White tinted (opal)	1.6	0.61	0.63
Quadruple pane, 51 mm			
Clear	1.3	0.60	0.61
Crystal structure	1.3	0.60	0.61
Grey tinted	1.3	0.02	0.23
Brown tinted	1.3	0.02	0.20
White tinted (opal)	1.3	0.54	0.58
Polycarbonate panes			
Single pane, 6 mm			
Clear	–	–	–
Double pane, 26 mm			
Clear	2.7	0.81	0.75
Real glass panes			
Single pane, 6 mm			
Clear	5.7	0.88	0.79
Double pane, 26 mm			
Clear	2.6	0.81	0.76
Climatic double pane, 26 mm			
Clear	1.1	0.80	0.64
Infill			
Multiple-moulded pane	1.9	0.57	0.59

Vitraplan attachments on request

Ug value Thermal insulation value
τ_v value Light transmission (transparency)
g-value Total energy transmittance

Construction and quality features

● = Standard
○ = Optional

	SPU F42	SPU 67 Thermo	APU F42	APU F42 Thermo	APU 67 Thermo	
Construction						
Self-supporting	●	●	●	●	●	
Depth, mm	42	67	42	42	67	
Door sizes						
Max. width mm, LZ	8000	10000	8000	7000	10000	
Max. height mm, RM	7500	7500	7500	7500	7500	
Material, door leaf						
Double-skinned steel section	●	–	●	●	–	
Double-skinned steel section with thermal break	–	●	–	–	●	
Aluminium profile	–	–	●	–	–	
Aluminium profile with thermal break	–	–	–	●	●	
Surface, door leaf						
Galvanized steel, coated RAL 9002	●	●	○	○	○	
Galvanized steel, coated RAL 9006	○	○	●	●	●	
Galvanized steel, coated RAL to choose	○	○	○	○	○	
Anodised aluminium E6 / C0	–	–	●	●	●	
Aluminium coated in RAL to choose	–	–	○	○	○	
Wicket door						
With trip-free threshold	○	○	○	○	○	
Side doors						
Side NT 60 matching the door	○	○	○	○	○	
Side door NT 80 Thermo matching the door	○	○	○	○	○	
Type A section window	○	○	–	–	–	
Type D section window	○	○	–	–	–	
Type E section windows	○	–	–	–	–	
Aluminium glazing frame	○	○	●	●	●	
Seals						
All-round on 4 sides	●	●	●	●	●	
Intermediate seal between the door sections	●	●	●	●	●	
ThermoFrame	○	○	○	○	○	
Locking systems						
Internal latches	●	●	●	●	●	
Outside / inside locking	○	○	○	○	○	
Anti-lift kit						
For doors of up to 5 m with shaft operator	●	●	●	●	●	
Safety equipment						
Finger trap protection	●	–	●	●	–	
Side trap guards	●	●	●	●	●	
Safety catch for doors	●	●	●	●	●	
Fastening options						
Concrete	●	●	●	●	●	
Steel	●	●	●	●	●	
Brickwork	●	●	●	●	●	
Others on request						

	ALR F42	ALR F42 Thermo	ALR 67 Thermo	ALR F42 Glazing	ALR 67 Thermo Glazing	ALR F42 Vitraplan
	● 42	● 42	● 67	● 42	● 67	● 42
	8000 7500	7000 7500	10000 7500	5500 4000	5500 4000	6000 7000
	– – ● –	– – – ●	– – – ●	– – ● –	– – – ●	– – ● –
	– – – ● ○	– – – ● ○	– – – ● ○	– – – ● ○	– – – ● ○	– – – – ●
	○	○	○	–	–	–
	○ ○	○ ○	○ ○	○ ○	○ ○	○ –
	– – – ●	– – – ●	– – – ●	– – – ●	– – – ●	– – – ●
	● ●	● ●	● ●	● ●	● ●	● ●
	○	○	○	○	○	○
	● ○	● ○	● ○	● –	● –	● –
	●	●	●	●	●	●
	● ● ●	● ● ●	– ● ●	● ● ●	– ● ●	● ● ●
	● ● ●	● ● ●	● ● ●	● ● ●	● ● ●	● ● ●

Hörmann product range

Everything from a single source for your construction project



Quick service with testing, maintenance and repairs
Our extensive service network means that we are always nearby and at your service around the clock.



1 **Sectional doors**

2 **Rolling shutters and rolling grilles**

3 **High-speed doors**

4 **Loading technology**

5 **Steel and stainless steel sliding doors**

6 **Steel and aluminium multi-function doors**

7 **Steel and stainless steel doors**

8 **Steel frames with high-quality timber function doors from Schörghuber**

9 **Fully glazed tubular frame parts**

10 **Automatic sliding doors**


11 **Visibility window**

12 **Collective garage doors**

GARAGE DOORS JUST GOT EUROPEAN.

Sectional Garage Doors

Roller Garage Doors

Residential Doors

Collective Garage Doors

Industrial Doors

Operators

High Speed Doors

Loading Technology

Rolling Shutters and Grilles

Hörmann is the only manufacturer worldwide that offers you a complete range of all major building products from one source. We manufacture in highly-specialised factories using the latest production technologies. The close-meshed network of sales and service companies throughout Europe, and activities in the USA and Asia, make Hörmann your strong partner for first-class building products, offering “Quality without Compromise”.

GARAGE DOORS

OPERATORS

INDUSTRIAL DOORS

LOADING EQUIPMENT

HINGED DOORS

DOOR FRAMES

4Ddoors

Just Got European

office@4ddoors.com ▪ www.4ddoors.com

HÖRMANN

Issue 03.2015 / Print 06.2015 / HF 86465 EN / PDF www.hoermann.com